

ABBREVIATIONS

A.	Automatic (of Transmissions)	kg m.	Kilograms Metric
ABDC.	After Bottom Dead Center	kv.	Kilo Volt(s)
AC.	Air Conditioning	LAC.	Less Air Conditioning
ac.	Alternating Current	lb.	Pound(s)
ACC.	Accessories	LHD.	Left Hand Drive
AGS.	Air Guard System	LT.	Light
AFR.	Air-Fuel-Ratio	M.	Manual
ALT.	Alternator	man.	Manual
AMC.	American Motors Corporation	max.	Maximum
amp.	Ampere	met.	Metallic
API.	American Petroleum Institute	mfd.	Microfarad
ATDC.	After Top Dead Center	min.	Minimum
AUTO.	Automatic	mph.	Miles Per Hour
B.	Battery	N.	Neutral
bat.	Battery	NA.	Not Available
BBDC.	Before Bottom Dead Center	NOx.	Oxides of Nitrogen
BC.	Bolt Circle (of Wheels)	no.	Number(s)
blk.	Black	O.	Optional
BTDC.	Before Top Dead Center	OD.	Outside Diameter
C.	Centigrade	OHV.	Over-Head Valve(s)
CARB.	Carburetor	opt.	Optional
CCW.	Counterclockwise	OS.	Oversize
cfh.	Cubic Feet Per Hour	P.	Park
cfm.	Cubic Feet Per Minute	pass.	Passenger(s)
CID.	Cubic Inch Displacement	PCV.	Positive Crankcase Ventilation
CL.	Center Line	POS.	Positive
comp.	Compression	psi.	Pounds Per Square Inch
conn.	Connector	psig.	Pounds Per Square Inch Gauge
CVR.	Constant Voltage Regulator	QT.	Quadra-Trac (Full Time Four Wheel Drive)
CW.	Clockwise	R.	Regular
cyl.	Cylinder	rev.	Revolution(s), Reverse, Revision
dc.	Direct Current	RHD.	Right Hand Drive
DIA.	Diameter	rpm.	Revolutions Per Minute
DIM.	Dimension	S.	Standard
DIST.	Distributor	SAE.	Society of Automotive Engineers
DR.	Door	SSR&O.	Special Sales Request and Order (Number)
EGR.	Exhaust Gas Recirculation	std.	Standard
EOS.	Engine Oil Supplement	SW.	Switch
EI.	Exhaust-Intake	TAC.	Thermostatically Controlled Air Cleaner
EPA.	Environmental Protection Agency	TCS.	Transmission Controlled Spark System
EXH.	Exhaust	TDS.	Top Dead Center
F.	Fahrenheit	TC.	Transfer Case
FEC.	Fuel Evaporative Control	Trans.	Transmission
Fig.	Figure(s)	TR.	Tracer
ft-lb.	Foot-Pound(s)	TVS.	Thermal Vacuum Switch
GAWR.	Gross Axle Weight Rating	US.	Undersize
gpm.	Gallons Per Minute	V.	Venturi
grn.	Green	V.	Volt(s)
GVW.	Gross Vehicle Weight	VAC.	Vacuum
GVWR.	Gross Vehicle Weight Rating	VAT.	Volts-Amperes-Tester
HD.	Heavy Duty	VIN.	Vehicle Identification Number
HG.	Mercury (Inches of)	w.	With
HT.	High Tension	WB.	Wheel Base
HR.	Hour(s)	w/.	With
Hz.	Hertz (electrical cycles per second)	W/AC.	With Air Conditioning
IE.	Intake-Exhaust	W/T.	Wire Tracer
ign.	Ignition		
ID.	Inside Diameter		
In-Lb.	Inch-Pound(s)		
in.	Inch		
IR.	Infrared		

DECIMAL EQUIVALENTS

1/64	.015625
1/32	.3125
3/64	.046875
1/16	.0625
5/64	.078125
3/32	.09375
7/64	.109375
1/8	.125
9/64	.140625
5/32	.15625
11/64	.171875
3/16	.1875
13/64	.203125
7/32	.21875
15/64	.234375
1/4	.25
17/64	.265625
9/32	.28125
19/64	.296875
5/16	.3125
21/64	.328125
11/32	.34375
23/64	.359375
3/8	.375
25/64	.390625
23/32	.40625
27/64	.421875
7/16	.4375
29/64	.453125
15/32	.46875
31/64	.484375
1/2	.5

33/64	.515625
17/32	.53125
35/64	.546875
9/16	.5625
37/64	.578125
19/32	.59375
39/64	.609375
5/8	.625
41/64	.640625
21/32	.65625
43/64	.671875
11/16	.6875
45/64	.703125
23/32	.71875
47/64	.734375
3/4	.75
49/64	.765625
25/32	.78125
51/64	.796875
13/16	.8125
53/64	.828125
27/32	.84375
55/64	.859375
7/8	.875
57/64	.890625
29/32	.90625
59/64	.921875
15/16	.9375
61/64	.953125
31/32	.96875
63/64	.984375
1	1

GAGES

GAGE NO.	U. S. STANDARD GAGE Approx. Thickness—Inches	AMERICAN WIRE or B & S GAGE Thickness—Inches
0000000	0.490	
000000	.460	0.5800
00000	.429	.5165
0000	.398	.4600
000	.368	.4096
00	.337	.3648
0	.306	.3248
1	.2757	.2893
2	.2604	.2576
3	.2451	.2294
4	.2298	.2043
5	.2145	.1819
6	.1991	.1620
7	.1838	.1443
8	.1685	.1285
9	.1532	.1144
10	.1379	.1019
11	.1225	.0907
12	.1072	.0808
13	.0919	.0720
14	.0766	.0641
15	.0689	.0571
16	.0613	.0508
17	.0551	.0453
18	.0490	.0403
19	.0429	.0359
20	.0368	.0320
21	.0337	.0285
22	.0306	.0253
23	.0276	.0226
24	.0245	.0201
25	.0214	.0179
26	.0184	.0159
27	.0169	.0142
28	.0153	.0126
29	.0138	.0113
30	.0123	.0100
31	.0107	.00893
32	.0100	.00795
33	.0092	.00708
34	.0084	.00630
35	.0077	.00561
36	.0069	.00500
37	.0065	.00445
38	.0061	.00397
39	.0057	.00353
40	.0054	.00314
41	.0052	
42	.0050	
43	.0048	
44	.0046	

WEIGHTS AND MEASURES

LINEAR MEASURE

1/12 foot (ft.) = 1 inch (in.)
12 inches = 1 foot
3 feet = 1 yard (1 yd.)

AREA MEASURE

1/144 square foot (sq. ft.) . . = 1 square inch (sq. in.)
144 square inches = 1 square foot
9 square feet = 1 square yard (sq. yd.)

LIQUID MEASURE

1/16 pint (pt.) = 1 ounce (oz.)
1 pint = 16 ounces
2 pints = 1 quart (qt.) = 32 ounces
4 quarts = 1 gallon (gal.)
31½ gallons = 1 barrel (bbl.)

DRY MEASURE

1/2 quart (qt.) = 1 pint (pt.)
2 pints = 1 quart (qt.)
8 quarts = 1 peck (pk.)
4 pecks = 1 bushel (bu.)
105 quarts = 1 barrel

CUBIC MEASURE

1,728 cubic inches = 1 cubic foot
27 cubic feet = 1 cubic yard

COMMON WEIGHT

16 ounces = 1 pound
100 pounds = 1 hundred weight (cwt.)
2000 pounds = 1 ton

COMMON U.S.A. EQUIVALENTS LENGTH

1 inch = 25.4001 millimeters
1 millimeter = 0.03937 inches
1 foot = 0.304801 meters
1 meter = 3.28083 feet
1 yard = 9.14402 meters
1 meter = 1.093611 yards
1 mile = 1.609347 kilometers
1 kilometer = 0.621370 miles

LIQUID CAPACITY

1 quart = 0.94633 liters
1 liter = 1.05671 quarts
1 gallon = 3.78533 liters
1 liter = 0.26418 gallons

DRY CAPACITY

1 quart = 1.1012 liters
1 liter = 0.9081 quarts
1 peck = 8.810 liters
1 liter = 0.11351 pecks

Fold Here

Cut Here

Do Not Tear — Fold Here and Staple

First Class
PERMIT
No. 1117
Detroit, Mich.

BUSINESS REPLY MAIL

No Postage Stamp Necessary if Mailed in the United States

— Postage will be paid by —

**JEEP CORPORATION
14250 PLYMOUTH ROAD
DETROIT, MICHIGAN 48232**



ATTENTION: SERVICE COMMUNICATIONS